

Range of MOTO-SPORT batteries / chargers

CONVENTIONAL WET OR DRY CHARGED BATTERIES

Part No	Ah	Length mm	Width mm	Height mm	Layout	Terminals	Varta Ref
YB4LB	4	121	71	92	0	2	504011
YB9B	9	137	77	138	1	2	509014
YB12AA	12	134	80	160	1	2	512011
YB12ALA2	12	134	80	160	0	2	512013
YB14AA2	14	135	90	176	0	2	514012
YB14LA2	14	135	90	167	0	2	514011
YB14B2	14	135	90	167	1	2	514014
YB16ALA2	16	204	70	164	0	2	516016
YB16B	19	173	99	156	1	2	519012
YB16CLB	19	173	99	175	0	2	519014
YB16LB	19	173	99	156	0	2	519011
Y50N18LA2	20	205	90	162	0	2	520012
Y60N30LA	28	185	129	168	0	2	530030
YB30CLB	30	178	130	190	0	2	n/a
895	24	186	125	171	0	2	n/a
896	24	186	125	171	1	2	n/a
895CXT (Sealed)	30	186	125	171	0	2	n/a
896CXT (Sealed)	30	186	125	171	1	2	n/a
897	24	186	125	171	0	1	n/a
898	24	186	125	171	1	1	n/a

HIGH PERFORMANCE GEL LIQIFIX BATTERIES

Part No	Ah	Length mm	Width mm	Height mm	Layout	Terminals	Varta Ref
YTR4ABS	2.3	113	38	86	4	Push On	n/a
YTX4LBS	3	113	70	86	0	2	503014
YTX7ABS	6	150	87	95	1	2	506015
YTX7LBS	6	113	70	130	0	2	506014
YTX9BS	8	150	87	105	1	2	508012
YTX12BS	10	150	88	130	1	2	510012
YTX14BS	12	150	87	146	1	2	512014
YTX15LBS	13	175	87	130	0	2	n/a
YTX16BS	14	150	88	161	0	2	514902
YTX18LBS	21	205	90	162	0	2	n/a
YTX20BS	18	175	87	154	1	2	518902
YTX20LBS	18	175	87	154	0	2	518901

VRLA SEALED BATTERIES

Part No	Ah	Length mm	Width mm	Height mm	Layout	Terminals	Varta Ref
YT4B5	2.5	113	38	86	4	Push On	n/a
YT4BBS	2.5	114	40	86	4	Push On	503902
YT4LBS	3	113	70	86	0	2	503014
YT5LBS	5	113	70	105	0	2	504012
YT6B3	6	113	70	106	0	2	n/a
YT7B4	6.5	150	66	92	1	2	n/a
YT9B4	8	150	69	105	1	2	509902
YT12ABS	10	151	87	106	1	2	511901
YT12B4	11	150	69	130	1	2	512901
YT14B4	13	150	69	144	1	2	512903
YTH1612	16	152	88	147	1	2	n/a
YTZ7S	6	113	70	106	0	2	507902
YTZ10S	8	150	87	93	1	2	508901
YTZ12S	11	150	87	110	1	2	509901
YTZ14S	11.2	150	87	110	1	2	511902

NUMAX AUTOMATIC BATTERY CHARGERS

Part No	VOLT	Amp	Length mm	Width mm	Height mm	Weight kgs
120100	12	1	105	40	30	0.35
120200	12	2	105	40	30	0.35

Range of INDUSTRIAL batteries

6 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US 1800	T605	208	260	181	286	UTL	25.4
US 2000	T6220	216	260	181	286	UTL	26.7
US 2200	T105	232	260	181	286	UTL	28.5
US2200DT	T105	232	260	181	286	DUAL	28.5
US125	T125	242	260	181	286	UTL	30.4
US125DT	T125	242	260	181	286	DUAL	30.4
US145	T145	251	260	181	302	DUAL	31.8
US250	J250P	258	295	181	295	DUAL	32.7
US250HC	N/A	283	295	181	295	DUAL	35.4
US305	J305P	305	302	181	371	DUAL	39.5
US305HC	J305H	335	302	181	371	DUAL	43.6
USL16	L16P	375	302	181	425	DUAL	51
USL16HC	L16H	415	302	181	425	DUAL	53

8 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US8VGC	T875	170	260	181	286	DUAL	29.5
US8VGCCHC	T875	183	260	181	286	DUAL	30.5

12 VOLT DEEP CYCLE US BATTERIES

Part No	Cross Ref	Ah/20hr	Length mm	Width mm	Height mm	Terminal	Weight kgs
US185	J185P	195	397	179	378	DUAL	49.5
US185HC	J185H	215	397	179	378	DUAL	54.4
US24TM	24TMX	85	273	171	248	DUAL	21.8
US27TM	27TMX	105	324	171	248	DUAL	24.5
US27TMX	27TMH	120	324	171	248	DUAL	24.5
US31TMX	30/31XHS	130	349	171	248	DUAL	29.9
EV145	J150	145	346	171	311	DUAL	39.5

ODYSSEY BATTERIES

Part No	Volt	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
PC310	12	8	100	155	137 x 86 x 101	2.7	M4 bolt	2
PC535	12	14.8	200	265	170 x 99 x 155	5.4	M6 bolt	0
PC545	12	14	170	240	178 x 86 x 132	5.7	M6 bolt	0
PC625	12	18	265	350	170 x 99 x 175	6.0	M6 stud	0
PC680	12	17	220	300	185 x 79 x 170	7.0	M6 bolt	0
PC925T	12	28	380	500	169 x 179 x 128	11.8	M6 bolt	0
PC1200T	12	44	550	725	200 x 170 x 173	17.4	M6 bolt	0
PC1500DT	12	68	825	1050	276 x 178 x 199	24.0	DUAL	1
PC1700T	12	68	875	1175	331 x 168 x 176	27.6	M6 bolt	0
PC2150T	12	100	1090	1370	330 x 173 x 239	34.1	9.5 stud	2
PC2250T	12	126	1225	1550	286 x 269 x 208	39.0	DUAL	0

OPTIMA BATTERIES

Part No	Volt	Ah/20hr	CCA (EN)	RC Mins	Dimensions L x W x H	Weight kgs	Terminals	Layout
RTS2.1	6	50	815	104	253 x 90 x 200	8.3	1	2
RTS3.7	12	44	730	90	237 x 172 x 194	15.0	1 and side	2
RTS4.2	12	50	815	104	256 x 174 x 200	17.6	1 and side	2
YTS2.7	12	41	510	70	234 x 127 x 227	11.6	1 or 3	0
YTS4.2	12	55	690	120	254 x 174 x 200	19.9	1 and side	2
YTS5.5	12	75	975	155	324 x 166 x 238	27.1	1	2

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469

Range of MOBILITY batteries / chargers

NUMAX DEEP CYCLE AGM BATTERIES

Part No	VOLT	Ah	Length mm	Width mm	Height mm	Weight kgs
SLA7-12	12	8	151	65	100	2.6
SLA12-12	12	12	151	95	101	4.1
SLC18-12	12	18	181	77	167	5.7
SLC22-12	12	22	181	77	167	5.8
SLC26-12	12	26	166	175	125	9.0
SLC34-12	12	34	195	130	180	10.2
SLC42-12	12	42	197	165	170	13.0
SLC75-12	12	75	260	168	233	25.5

YUASA DEEP CYCLE AGM BATTERIES

Part No	VOLT	Ah/20hr	Length mm	Width mm	Height mm	Weight kgs
Y7-12	12	7	151	65	100	2.60
Y12-12	12	12	151	95	101	4.10
YC17-12	12	17	181	76	167	6.1
YC20-12	12	20	181	76	167	6.1
YC24-12	12	24	166	175	125	9.0
YC33-12	12	30	195	129	179	11.2
YC38-12	12	38	197	165	170	15.0
YC50-12	12	50	228	138	228	17.5
Y65-12	12	65	350	166	174	23.0
YC70-12	12	70	258	168	228	24.5
YC100-12	12	100	344	171	280	39.0

NUMAX DEEP CYCLE GEL BATTERIES

Part No	VOLT	Ah/20hr	Length mm	Width mm	Height mm	Weight kgs
SLG26-12	12	26	166	175	125	9.0
SLG34-12	12	34	195	130	180	10.5
SLG42-12	12	42	197	165	170	13.8
SLG63-12	12	63	260	168	233	20.8
SLG75-12	12	75	260	168	233	26.0
SLG104-12	12	104	330	171	224	32.5

SONNENSCHN DEEP CYCLE GEL BATTERIES

Part No	VOLT	Ah/20hr	Length mm	Width mm	Height mm	Weight kgs
GF12022YF	12	24	167	176	126	9.6
GF12025YG	12	28	197	132	180	11.1
GF12033YG2	12	38	210	175	175	14.6
GF12051Y1	12	56	278	175	190	21.8
GF12063YO	12	70	260	171	210	23.0
GF12065Y	12	75	353	175	190	26.0

NUMAX AUTOMATIC CHARGERS

Part No	VOLT	Amp	Dimensions L x W x H	Weight kgs
120100	12	1	105 x 40 x 30	0.35
120200	12	2	105 x 40 x 30	0.35
120400	12	4	155 x 70 x 48	0.5
121000	12	10	167 x 103 x 50	0.9

MANBAT HF MOBILITY CHARGERS

Part No	VOLT	Amp	Dimensions L x W x H	Weight kgs
240400	24	4	155 x 70x 48	0.5
240700	24	7	167 x 103 x 50	0.9

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469

Range of LEISURE batteries / chargers

NUMAX LEISURE FLOODED BATTERIES

Part No	VOLT	Ah/20hr	RC Mins	CCA (0°F)	Dimensions L x W x H	Weight kgs	Terminals	Layout
L85	12	85	120	600	256 x 175 x 230	19.0	1	1
L110	12	110	200	700	345 x 175 x 226	29.5	1	1
L135	12	135	230	800	346 x 175 x 289	42.5	1	1

NUMAX SEALED LEISURE FLOODED BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
XV22MF	12	70	130	550	205 x 132 x 185	14.5	1	1
XV24MF	12	86	155	800	257 x 172 x 220	18.1	DT	1
XV25MF	12	90	158	800	354 x 175 x 175	22.6	1	1
XV27MF	12	105	160	800	302 x 172 x 220	22.4	DT	1
XV31MF	12	113	180	800	330 x 172 x 242	24.9	DT	3
XV50MF	12	120	230	900	506 x 182 x 249	35.4	1	3
XV60MF	12	170	300	1000	506 x 212 x 249	41.2	1	3
XV70MF	12	205	430	1200	509 x 274 x 256	55.7	1	3
XV80MF	12	235	500	1400	509 x 274 x 256	62.3	1	3

NUMAX AGM LEISURE (CYCLIC) BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
SLC85-12	12	85	180	780	260 x 168 x 233	24.5	1/F17	1
SLC120-12	12	120	250	950	331 x 171 x 214	33.0	1/F17	1
SLC150-12	12	150	280	1050	485 x 172 x 240	37.5	1/F17	1
SLC160-12	12	160	300	1190	341 x 173 x 308	47.5	1/F17	1
SLC200-12	12	200	450	1290	522 x 238 x 218	65.0	1/F17	3
SLC260-12	12	260	530	1375	522 x 269 x 220	76.5	1/F17	3

NUMAX AGM LEISURE (STARTING) BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
SLS70-12	12	70	140	760	278 x 175 x 190	20.2	1	0
SLS95-12	12	95	190	850	333 x 175 x 190	26.4	1	0

NUMAX AUTOMATIC BATTERY CHARGERS

Part No	VOLT	Amp	Dimensions L x W x H	Weight kgs
121000	12	10	167 x 103 x 50	0.9
122000	12	20	190 x 118 x 58	1.7
123000	12	30	152 x 70 x 275	2.4

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469

Range of MARINE batteries / chargers

NUMAX MARINE FLOODED BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
M85	12	85	600	720	256 x 175 x 230	19.0	1	1
M110	12	110	700	850	345 x 175 x 226	29.5	1	1
M135	12	135	800	975	346 x 175 x 289	42.5	1	1
M140	12	140	800	975	513 x 185 x 215	42.5	1	3
M180	12	180	1210	1475	513 x 225 x 225	44.5	1	3
M225	12	225	1040	1250	518 x 276 x 240	67.0	1	3

NUMAX SEALED MARINE FLOODED BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
XV22MF	12	70	550	685	205 x 132 x 185	14.5	1	1
XV24MF	12	86	800	1000	257 x 172 x 220	18.1	DT	1
XV27MF	12	105	800	1000	302 x 172 x 220	22.4	DT	1
XV31MF	12	113	800	1000	330 x 172 x 242	24.9	DT	3
XV50MF	12	120	900	1125	506 x 182 x 249	35.4	1	3
XV60MF	12	170	1000	1200	506 x 212 x 249	41.2	1	3
XV70MF	12	205	1200	1500	509 x 274 x 256	55.7	1	3
XV80MF	12	235	1400	1800	509 x 274 x 256	62.3	1	3

NUMAX AGM MARINE BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
SLC85-12	12	85	780	950	260 x 168 x 233	24.5	1/F17	1
SLC120-12	12	120	950	1150	331 x 171 x 214	33.0	1/F17	1
SLC150-12	12	150	1050	1200	485 x 172 x 240	37.5	1/F17	1
SLC160-12	12	160	1190	1450	341 x 173 x 308	47.5	1/F17	1
SLC200-12	12	200	1290	1575	522 x 238 x 218	65.0	1/F17	3
SLC260-12	12	260	1375	1700	522 x 269 x 220	76.5	1/F17	3

NUMAX GEL MARINE BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
SLG 34-12	12	34	300	375	195 x 130 x 180	11.3	1/F15	1
SLG75-12	12	75	750	900	260 x 168 x 233	26.5	1/F17	1
SLG104-12	12	104	900	1080	330 x 171 x 224	32.5	1/F17	1
SLG140-12	12	140	1050	1260	342 x 172 x 280	47.0	1	1
SLG180-12	12	180	1250	1525	494 x 206 x 280	59.0	1	3
SLG200-12	12	200	1300	1610	522 x 238 x 220	66.0	1	3
SLG250-12	12	250	1450	1740	521 x 269 x 220	89.0	1	3

ODYSSEY BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
PC310	12	8	100	155	137 x 86 x 101	2.7	M4 bolt	2
PC535	12	14.8	200	265	170 x 99 x 155	5.4	M6 bolt	0
PC545	12	14	170	240	178 x 86 x 132	5.7	M6 bolt	0
PC625	12	18	265	350	170 x 99 x 175	6.0	M6 stud	0
PC680	12	17	220	300	185 x 79 x 170	7.0	M6 bolt	0
PC925T	12	28	380	500	169 x 179 x 128	11.8	M6 bolt	0
PC1200T	12	44	550	725	200 x 170 x 173	17.4	M6 bolt	0
PC1500DT	12	68	825	1050	276 x 178 x 199	24.0	DUAL	1
PC1700T	12	68	875	1175	331 x 168 x 176	27.6	M6 bolt	0
PC2150T	12	100	1090	1370	330 x 173 x 239	34.1	9.5 stud	2
PC2250T	12	126	1225	1550	286 x 269 x 208	39.0	DUAL	0

OPTIMA SPIRAL BATTERIES

Part No	VOLT	Ah/20hr	CCA (-18°C)	MCA (0°C)	Dimensions L x W x H	Weight kgs	Terminals	Layout
BTDCM4.2	12	55	690	860	254 x 174 x 200	19.7	DUAL	1
BTDSLIM4.2	12	50	815	1010	254 x 174 x 200	17.4	DUAL	1
BTDCM5.5	12	75	975	1220	324 x 166 x 238	27.3	DUAL	7

NUMAX AUTOMATIC BATTERY CHARGERS

Part No	VOLT	Amp	Dimensions L x W x H	Weight kgs
121000	12	10	167 x 103 x 50	0.9
122000	12	20	190 x 118 x 58	1.7
123000	12	30	152 x 70 x 275	2.4

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469

Range of GOLFING batteries / chargers

US BATTERY DEEP CYCLE LEAD ACID RIDE-ON GOLF BUGGY BATTERIES

Part No	VOLT	Ah	Length mm	Width mm	Height mm	Weight kgs
US1800	6	208	260	181	286	25.4
US2000	6	216	260	181	286	26.7
US2200	6	232	260	181	286	28.5
US125	6	242	260	181	286	30.4
US145	6	251	260	181	302	31.8
US8VGC	8	165	260	181	286	29.5
US8VGCHC	8	178	260	181	286	30.5

NUMAX DEEP CYCLE SEALED GEL BATTERIES

Part No	VOLT	Ah	Length mm	Width mm	Height mm	Weight kgs
SLG26-12	12	26	166	175	125	9.0
SLG26-12G	12	26	166	175	125	9.1
SLG34-12	12	34	195	130	180	10.5
SLG75-12	12	75	260	168	233	26.0
SLG104-12	12	104	330	171	224	32.0

NUMAX DEEP CYCLE VRLA BATTERIES

Part No	VOLT	Ah	Length mm	Width mm	Height mm	Weight kgs
SLC22-12	12	22	181	77	167	5.8
SLC26-12	12	26	166	175	125	9.0
SLC26-12G	12	26	166	175	125	9.1
SLC34-12	12	34	195	130	180	10.2
SLC42-12	12	42	197	165	170	13.05

NUMAX GOLF CHARGERS AND ACCESSORIES

Part No	Description	VOLT	Amp	Length mm	Width mm	Height mm	Weight kgs
120400	Golf Charger	12	4	155	70	48	0.5
PKA18	PK Adaptor for 24 - 26 Ah Batteries						
PKA36	PK Adaptor for 28 - 34 Ah Batteries						
PKT	PK charger T piece						
HBC	HB connector						

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469

Range of VRLA batteries / chargers

NUMAX AGM DEEP CYCLE

Part No	VOLT	Ah /20hr	Dimensions L x W x H	Weight kgs
SLA7-12	12	8	151 x 65 x 100	2.60
SLA12-12	12	12	151 x 98 x 101	4.10
SLC18-12	12	20	181 x 77 x 167	5.80
SLA20-12	12	18	181 x 77 x 167	5.70
SLC22-12	12	22	181 x 77 x 167	5.80
SLC26-12	12	26	166 x 175 x 125	9.00
SLC34-12	12	34	195 x 130 x 180	10.20
SLC42-12	12	40	197 x 165 x 170	13.00
SLC75-12	12	75	260 x 168 x 233	25.50
SLC85-12	12	85	260 x 168 x 233	26.00
SLC120-12	12	120	331 x 171 x 214	33.00
SLC150-12	12	150	485 x 172 x 240	37.50
SLC160-12	12	160	341 x 173 x 308	47.50
SLC200-12	12	200	522 x 238 x 218	65.00
SLC260-12	12	260	522 x 269 x 220	76.50

NUMAX GEL DEEP CYCLE

Part No	VOLT	Ah /20hr	Dimensions L x W x H	Weight kgs
SLG34-12	12	34	195 x 130 x 180	10.50
SLG42-12	12	42	197 x 165 x 170	13.80
SLG75-12	12	75	260 x 168 x 233	26.00
SLG-104-12	12	104	330 x 171 x 224	32.50
SLG140-12	12	140	342 x 172 x 280	47.00
SLG180-12	12	180	494 x 207 x 220	59.00
SLG200-12	12	200	522 x 238 x 220	47.50
SLG250-12	12	250	522 x 269 x 220	66.00

SONNENSCHN GEL DEEP CYCLE

Part No	VOLT	Ah /20hr	Dimensions L x W x H	Weight kgs
GF06180V	6	180	244 x 190 x 282	30.0
GF12014YF	12	15	181 x 76 x 167	6.8
GF12022YF	12	24	167 x 176 x 126	11.7
GF12025YG	12	28	197 x 132 x 184	11.7
GF12033Y1	12	38	210 x 175 x 175	14.8
GF12033YG2	12	38	210 x 175 x 175	14.8
GF12033Y1	12	40	210 x 175 x 175	14.8
GF12040Y	12	48	242 x 175 x 190	19.0
GF12044Y	12	52	261 x 135 x 230	18
GF12051Y2	12	56	278 x 175 x 190	21.8
GF12051Y1G	12	56	278 x 175 x 190	21.8
GF12051Y2	12	57	278 x 175 x 190	21.8
GF12063Y	12	75	260 x 171 x 210	23.0
GF12065Y	12	75	353 x 175 x 190	26.8
GF12072Y	12	80	330 x 171 x 236	33.0
GF12094Y	12	110	284 x 267 x 230	40.3
GF12090V	12	115	513 x 189 x 223	40.7
GF12100V	12	120	345 x 174 x 283	40.5
GF12110V	12	135	513 x 223 x 225	47.8
GF12160V	12	200	518 x 274 x 242	70.0

YUASA AGM LONG LIFE

NP	Y	VOLT	Ah /20hr	Dimensions L x W x H	Weight kgs
NP1-6	Y1-6	6	1.0	51 x 43 x 55	0.25
NP1.2-6	Y1.2-6	6	1.2	97 x 25 x 55	0.31
NP2.8-6	Y2.8-6	6	2.8	134 x 34 x 64	0.57
NP4-6	Y4-6	6	4.0	70 x 47 x 106	0.87
NP7-6		6	7.0	151 x 34 x 98	1.32
NP10-6	Y10-6	6	10.0	151 x 50 x 98	1.93
NP12-6	Y12-6L	6	12.0	151 x 50 x 98	2.05
NP0.8-12	Y0.812	12	0.8	96 x 25 x 62	0.35
NP1.2-12	Y1.2-12	12	1.2	97 x 48 x 55	0.58
NP2-12		12	2.0	150 x 20 x 89	0.70
NP2.1-12	Y2.1-12	12	2.1	178 x 34 x 64	0.82
NP2.3-12	Y2.3-12	12	2.3	178 x 34 x 64	0.95
NP2.7-12	GS2.7-12	12	2.7	78 x 54 x 101	1.13
NP2.8-12	Y2.8-12	12	2.8	134 x 67 x 64	1.12
NP3.2-12	Y3.2-12	12	3.2	134 x 67 x 64	1.20
NP4-12	Y4-12	12	4	90 x 70 x 106	1.75
NP7-12	Y7-12	12	7	151 x 65 x 98	2.65
NP12-12	Y12-12	12	12	151 x 98 x 98	4.05
NP17-12	Y17-12i	12	17	181 x 76 x 167	6.10
NP18-12		12	18	181 x 76 x 167	6.20
NP24-12	Y24-12i	12	24	166 x 175 x 125	9.00
NP38-12	Y38-12i	12	38	197 x 165 x 170	14.20
NP65-12	Y65-12i	12	65	350 x 166 x 174	23.00
	Y100-12	12	110	344 x 171 x 280	39.00
	Y150-12	12	166	485 x 170 x 242	42.50
	Y200-12	12	210	522 x 240 x 224	64.00

YUASA AGM DEEP CYCLE

NPC	YC	VOLT	Ah /20hr	Dimensions L x W x H	Weight kgs
NPC17-12	YC17-12	12	17	181 x 76 x 167	6.10
	YC20-12	12	20	181 x 76 x 167	6.20
NPC24-12	YC24-12	12	24	166 x 175 x 125	9.00
NPC30-12	YC33-12	12	30	195 x 129 x 179	11.20
NPC38-12	YC38-12	12	38	197 x 165 x 170	15.00
	YC50-12	12	50	228 x 138 x 228	17.50
NPC65-12		12	65	350 x 166 x 174	23.00
	YC70-12	12	70	260 x 170 x 230	24.50
	YC100-12	12	100	344 x 171 x 280	39.00

NUMAX AUTOMATIC BATTERY CHARGERS

Part No	VOLT	Amp	Dimensions L x W x H	Weight kgs
120100	12	1	105 x 40 x 30	0.35
120200	12	2	105 x 40 x 30	0.35
120400	12	4	155 x 70 x 48	0.5
121000	12	10	167 x 103 x 50	0.9
122000	12	20	190 x 118 x 58	1.7
123000	12	30	152 x 70 x 275	2.4
240400	24	4	155 x 70 x 48	0.5
240700	24	7	167 x 103 x 50	0.9

Battery Solutions York Ltd

75 Leeman Road, YO26 4XH - Telephone: 01904 626414 - Fax: 01904 652469